



858
Bark

DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Textured Patterned Multi-Colored Loop
Gauge:	1/12 (47.00 rows per 10cm)
Tufted Pile Weight:	24 oz/yd ² (814 g/m ²)
Finished Pile Thickness:	.156" (3.96 mm)
Total Thickness:	.183" (4.65 mm)
Stitches Per Inch:	9.4 (37.01 per 10cm)
Dye Method:	Solution Dyed
Fiber Type:	Duracolor® Tricor Premium Nylon
Stain Release Technology:	Permanent, Built into the Fiber
Soil Release Technology:	EcoSentry Soil Protection
Density:	5,538
Weight Density:	132,923
Backing Material:	EcoFlex ONE
Installation Method:	Monolithic, Half Lap, Brick Ashlar, Basket Weave, Plank Half Lap, Monolithic Stepping, Random, Herringbone
Size:	12" x 36" (.3048 m x .9144 m)

SUSTAINABILITY

NSF 140:	NSF 140 Platinum
Indoor Air Quality:	CRI Green Label Plus GLP1171

PERFORMANCE

Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC - 134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Heavy

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Duracolor Stain Warranty, Lifetime Static
-------------	---