

Entwined Collection

Style	Husk (Modular)	Moso (Modular)	Ramie (Modular)
Construction	Textured Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution/Yarn	Solution/Yarn	Solution/Yarn
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	10 (39.37 per 10 cm)	9.50 (37.40 per 10 cm)	9.83 (38.70 per 10 cm)
Density	5,657 (210.20 kg/m³)	5,657 (210.20 kg/m³)	5,657 (210.20 kg/m³)
Pile Thickness	0.140" (3.56 mm)	0.140" (3.56 mm)	0.140" (3.56 mm)
Weight	22 oz/yd² (746 g/m²)	22 oz/yd² (746 g/m²)	22 oz/yd² (746 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular	Infinity® 2 Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	12	12	12
Packaging	8 yd² / 18 Tiles	8 yd² / 18 Tiles	8 yd² / 18 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Horizontal Brick Ashlar, Monolithic	Horizontal Brick Ashlar, Monolithic	Horizontal Brick Ashlar, Monolithic
Testing			
Dimensional Stability (Aachen Test)	Passes	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	Passes - Class 1; ≥ 0.45 watts/cm²	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes	Passes
Hexapod (ASTM D5252) TARR	4	3.5	4
Environmental Data			
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold		
Recycled Content	Contains recycled content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	EPD, HPD		
LEED	Building Product Disclosure & Optimization - EPDs		
	Building Product Disclosure & Optimization - Sourcing Raw Materials		
	Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered		
Warranty			
	Limited Lifetime Wear & Backing Warranty		
	Limited 15-Year XGUARD® Stain Resistant Warranty		
	Limited 15-Year ColorSafe® Bleach Resistant Warranty		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.