

Connected Collection

Style	Media (Modular)	Offline (Modular)	Offline Loop (Modular)
Construction	Tip-sheared Patterned Loop	Tip-sheared Patterned Loop	Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	
Dye Method	Solution	Solution	Type 6,6 Nylon
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	Solution
Stitches Per Inch	9.66 (38.03 per 10 cm) 6,468	9.66 (38.03 per 10 cm) 6,545	5/64 (50.39 per 10 cm)
Density	(240.34 kg/m ³)	(243.20 kg/m ³)	9.66 (38.03 per 10 cm)
Pile Thickness	0.128" (3.25 mm)	0.121" (3.07 mm)	6,655 (247.29 kg/m ³)
Weight	23 oz/yd ² (780 g/m ²)	22 oz/yd ² (746 g/m ²)	0.119" (3.02 mm)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular	22 oz/yd ² (746 g/m ²)
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)	Infinity® 2 Modular
Colors	16	16	24" x 24" (60.96 x 60.96 cm)
Packaging	8 yd ² / 18 Tiles	8 yd ² / 18 Tiles	16
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive	8 yd ² / 18 Tiles
Installation Method	Horizontal Brick Ashlar	Vertical Ashlar	Infinity 2 Adhesive Vertical Ashlar
Testing			
Dimensional Stability (Aachen Test)	Passes		
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²		
Smoke Density (ASTM E662)	Passes - ≤ 450		
Methenamine Pill Test (ASTM D2859)	Passes		
Hexapod (ASTM D5252) TARR	3.5		
Environmental Data			
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold		
Recycled Content	Contains recycled content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	EPD, HPD		
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered		
Warranty			
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Connected Collection

Style	Online (Modular)	Profile (Modular)	Social (Modular)
Construction	Tip-sheared Patterned Loop	Tip-sheared Patterned Loop	Tip-sheared Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	9.66 (38.03 per 10 cm) 6,468	9.66 (38.03 per 10 cm) 6,786	9.66 (38.03 per 10 cm) 6,545
Density	(240.34 kg/m³)	(252.15 kg/m³)	(243.20 kg/m³)
Pile Thickness	0.128" (3.25 mm)	0.122" (3.10 mm)	0.121" (3.07 mm)
Weight	23 oz/yd² (780 g/m²)	23 oz/yd² (780 g/m²)	22 oz/yd² (746 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular	Infinity® 2 Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	16	16	16
Pattern Repeat	N/A	N/A	N/A
Packaging	8 yd² / 18 Tiles	8 yd² / 18 Tiles	8 yd² / 18 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Horizontal Brick Ashlar	Horizontal Brick Ashlar and Vertical Ashlar	Horizontal Brick Ashlar and Vertical Ashlar

Testing

Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	3.5

Environmental Data

NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered

Warranty

Limited Lifetime Wear & Backing Warranty
Limited 15-Year XGUARD® Stain Resistant Warranty Limited
15-Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.