

Urban Grid Collection

Style	Mesh (Broadloom)	Mesh (Modular)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	ECONYL® 100% Regenerated Type 6 Nylon	ECONYL® 100% Regenerated Type 6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	10.33 (40.67 per 10 cm)	9 (35.43per 10 cm)
Density	5,538 (205.78 kg/m³)	5,305 (197.12 kg/m³)
Pile Thickness	0.104" (2.64 mm)	0.095" (2.41 mm)
Weight	16 oz/yd² (542 g/m²)	14 oz/yd² (475 g/m²)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12'6" (3.81 m)	18" x 36" (45.72 x 91.44 cm)
Colors	8	8
Pattern Repeat	Random Pattern Match	N/A
Packaging	N/A	8 yd² / 16 tiles
Adhesive	Ultra Adhesive Integra-2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Horizontal Brick Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5	
Environmental Data		
NSF / ANSI-140 Certification	UltraBac® RE - Platinum, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	EPD, HPD	
Carbon Offset	Carbon Offset 105% (Cradle to Gate (A1-A3); 13.87kg CO2e/yd²)	
LEED Scoreboard	LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified	
Warranty		
	Limited Lifetime Wear & Backing	
	Limited 15 Year XGUARD® Stain Resistant	
	Limited 15 Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Urban Grid Collection

Style	Scaffold (Broadloom)	Scaffold (Modular)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	ECONYL® 100% Regenerated Type 6 Nylon	ECONYL® 100% Regenerated Type 6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	10.66 (41.97 per 10 cm)	9.33 (36.73 per 10 cm)
Density	5,538 (205.78 kg/m³)	5,305 (197.12 kg/m³)
Pile Thickness	0.104" (2.64 mm)	0.095" (2.41 mm)
Weight	16 oz/yd² (542 g/m²)	14 oz/yd² (475 g/m²)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12'6" (3.81 m)	18" x 36" (45.72 x 91.44 cm)
Colors	8	8
Pattern Repeat	Random Pattern Match	N/A
Packaging	N/A	8 yd² / 16 tiles
Adhesive	Ultra Adhesive Integra-2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Horizontal Brick Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5	
Environmental Data		
NSF/ANSI 140 Certification	UltraBac® RE - Platinum, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	EPD, HPD	
Carbon Offset	Carbon Offset 105% (Cradle to Gate (A1-A3); 13.87kg CO2e/yd²)	
LEED Scoreboard	LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.org/build , for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified	
Warranty		
	Limited Lifetime Wear & Backing	
	Limited 15 Year XGUARD® Stain Resistant	
	Limited 15 Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Urban Patina Collection

Style	Elevation (Modular)	Span (Modular)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	ECONYL® 100% Regenerated Type 6 Nylon	ECONYL® 100% Regenerated Type 6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	9.16 (36.06 per 10 cm)	8.83 (34.76 per 10 cm)
Density	5,538 (205.78 kg/m³)	5,538 (205.78 kg/m³)
Pile Thickness	0.091" (2.31 mm)	0.091" (2.31 mm)
Weight	14 oz/yd² (475 g/m²)	14 oz/yd² (542 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular
Sizes	18" x 36" (45.72 x 91.44 cm)	18" x 36" (45.72 x 91.44 cm)
Colors	8	8
Packaging	8 yd² / 16 tiles	8 yd² / 16 tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Horizontal Brick Ashlar, Monolithic, Vertical Ashlar	Horizontal Brick Ashlar, Monolithic, Vertical Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5	
Environmental Data		
NSF/ANSI 140 Certification	UltraBac® RE - Platinum, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	EPD, HPD	
Carbon Offset	Carbon Offset 105% (Cradle to Gate (A1-A3); 13.87kg CO2e/yd²)	
LEED Scoreboard	LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Certified	
Warranty		
	Limited Lifetime Wear & Backing	
	Limited 15 Year XGUARD® Stain Resistant	
	Limited 15 Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.