



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Tufted Pile Weight:	17.0 oz. per sq. yd. (576 g/m ²)
Finished Pile Thickness:	.095" (2.41 mm)
Total Thickness:	.255" (6.48 mm)
Stitches Per Inch:	11.0 (43.34 per 10 cm)
Dye Method:	Solution Dyed / Yarn Dyed
Fiber Type:	Colorstrand® Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	6,442
Weight Density:	109,515
Backing Material:	EcoFlex Matrix
Alternate Backing:	EcoFlex AIR - Minimum SY Required
Installation Method:	Monolithic, Vertical Ashlar, Brick Ashlar, Quarter Turn, Multi Directional
Size:	24" x 24" (.6096 m x .6096 m)
Pattern Repeat:	Not Applicable

SUSTAINABILITY

Pre-Consumer Recycled Content:	48%
NSF 140:	EcoFlex Matrix - NSF 140 Gold
Indoor Air Quality:	CRI Green Label Plus GLP1171
Declare Label:	Declared Red List Free

PERFORMANCE


Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Severe

SERVICE


Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Static
-------------	--




131
Madras
Quickship Available




585
Sea Breeze
Quickship Available



878
Mudslide
Quickship Available



968
Smoky Martini
Quickship Available



989
Black Velvet
Quickship Available