## Mohawk Group

## Healthy Environments Collection

## GT406 Xeric Tile 12BY36

Mohawk Group





867 Acoma



951 Acacia



956 Pinyon



877 Hopi

955 Larkspur



957 Mesa



947 Cholla

959 Kofa

Product Type:	Tile
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Tufted Pile Weight:	22 oz/yd2 (746 g/m2)
Finished Pile Thickness:	.099" (2.51 mm)
Stitches Per Inch:	12.0 (47.24 per 10 cm)
Dye Method:	Solution Dyed
Fiber Type:	Duracolor® Tricor Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permane stain resistant carpet.
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	EcoSentry Soil Treatment
Density:	8,000
Weight Density:	176,000
Backing Material:	EcoFlex NXT
Installation Method:	Brick Ashlar, Random, Herringbone
Size:	12" x 36" (.3048 m x .9144 m)
Pattern Repeat:	Not Applicable
SUSTAINABILITY Pre-Consumer Recycled Content:	57%
	57% EcoFlex NXT - NSF 140 Gold
Pre-Consumer Recycled Content:	
Pre-Consumer Recycled Content: NSF 140:	EcoFlex NXT - NSF 140 Gold
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label:	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label: <b>PERFORMANCE</b>	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label:	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171 Declared Red List Free
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label: <b>PERFORMANCE</b> Flammability: Smoke Density:	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171 Declared Red List Free ASTM E 648 Class 1 (Glue Down)
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label: <b>PERFORMANCE</b> Flammability:	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171 Declared Red List Free ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label: PERFORMANCE Flammability: Smoke Density: Static Propensity: Foot Traffic Recommendation TARR:	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171 Declared Red List Free ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450 AATCC-134 Under 3.5 KV
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label: PERFORMANCE Flammability: Smoke Density: Static Propensity:	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171 Declared Red List Free ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450 AATCC-134 Under 3.5 KV Severe
Pre-Consumer Recycled Content: NSF 140: Indoor Air Quality: Declare Label: PERFORMANCE Flammability: Smoke Density: Static Propensity: Foot Traffic Recommendation TARR:	EcoFlex NXT - NSF 140 Gold CRI Green Label Plus GLP1171 Declared Red List Free ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450 AATCC-134 Under 3.5 KV Severe



Healthy Environments Collection

GT406 Xeric Tile 12BY36

Mohawk Group



993 Zuni