


Keglen

15.7 IN / 21W LED/3000K / 120-277V/60HZ / Black / Black textile and wire / - / Phase+dim 0-10v / - / 10000151384

The pendants distinctive conical shades each have a built-in curved opal insert. This ensures a both attractive and glare-free downward light. Each version of the shade provides its own diffusion of light while the white inner side ensures that its light is reflected flawlessly. A gentle light is also emitted upwards through a uniform, discreet opening in the top of the shades which adds to the perfect ambiance.



Jakob Lange - BIG Ideas



Product info

Information

Electrical: System Wattage: 6W, 8W, 21W or 31W LED Wattage: 5W, 7W, 19W, or 29W Delivered lumens: 276 - 2,254 lm Efficacy: 50 lm/W - 73 lm/W Certifications: cULus, Damp location Controllability: 0-10V Dimming Color Rendering: Ra≥90

Mounting

Suspension type: 1x black stainless steel aircraft cable. Cord type: 18 AWG braided fabric covered power cord. Cord length: 12'. Black canopy and cord for black pendant, white canopy and cord for white pendant.

Finish

Black or white, matte, wet painted.

Materials

Shade: Spun aluminum. Diffusor: Injection molded PC.

Sizes and weight

Width x Height x Length (in.) | 15.7 x 10.6 x 15.7 Max 10.8 lbs | 6.9 x 5.3 x 6.9 Max 5.4 lbs | 9.8 x 10.6 x 9.8 Max 3.7 lbs | 25.6 x 10.6 x 25.6 Max 14.5 lbs

Compliance

cULus, Damp location.

Specification notes

a. 6.9 IN size available only in 6W. B. 9.8 IN size available only in 8W. c. 15.7 IN size available only in 21W. c. 25.6 IN size available only in 21W. d. White variants come with white cord and canopy, black variants come with black cord and canopy.

Light source

21W LED/3000K
Lumen: 1231

Information

Electrical:
System Wattage: 6W, 8W, 21W or 31W
LED Wattage: 5W, 7W, 19W, or 29W
Delivered lumens: 276 - 2,254 lm
Efficacy: 50 lm/W - 73 lm/W
Certifications:
cULus, Damp location
Controllability: 0-10V Dimming
Color Rendering: Ra≥90



Product family



Keglen Table




Keglen Wall




Keglen Floor

Light distribution diagrams


Cartesian



Isolux



Polar



Spare parts & accessories

Product	Variant number
CANOPY SHADE BLACK KEGLN	10000151814
CANOPY SHADE WHITE KEGLN	10000151815

Data specifications

Colour	Black	Length	15.7
Width	15.7	Height	10.6
Built-in Height	-	IP class	20
Class	-	Net Weight	10.8
Standby (W)	-	Power Factor (P = 100 % / P = 50 %)	-

Keglen

Inrush Current	-
Kelvin	3000
SDCM	3
Watt	21
Light control	Phase+dim 0-10v
UGR Transversal / Axial	20.2/20.2
Driver life	-

Light source	21W LED/3000K
CRI	90
Lumen	1231
Efficacy	59
Min. Dim Level (%)	10
L80B50 (hours)	-