

Declare.



VAPOR ECHO (LX-VE)


TYPE:


KEY BENEFITS


- Highly effective noise absorption
- Available in 3 sizes and a wide range of
- High performance dimmable LED light source (Direct)
- Optional upwards dimmable LED wash lighting available (Indirect)
- Height adjustable 9' / 3m suspension cables and Black woven power cable
- 0.1% dimming option available
- POE available on request

- IES photometric files available
- Bluetooth controller available upon request (only for US and EU)
- Can be mounted flush to ceiling
- L70 lifetime rating of 50,000 hours
- White canopy and power cord available upon request
- Flatpack version available for Large size
- Tunable White ouput available upon inquiry
- Available in the printed MOTIF collection

SIZE, OUTPUT AND WEIGHT







	SMALL		MEDIUM			LARGE			
Output	Delivered Lumens	Wattage	Efficacy _{lm/W}	Delivered Lumens	Wattage	Efficacy lm/W	Delivered Lumens	Wattage	Efficacy _{lm/W}
Direct OR Indirect	1680	19	88	4500	57	79	4500	57	79
Direct AND Indirect	-	-	-	9000	114	79	9000	114	79
Weight	17.6 lbs / 8 Kg		30.8 lbs / 14 Kg			66.1 lbs / 30 Kg			

ORDER CODE

EXAMPLE: LX - VE - L - R - 40 - DI - UNV - RD

 $(Luxxbox\ Vapor\ Echo,\ Large\ (dia\ 60"\ x\ 24.4"\ /\ 1500\ x\ 620mm),\ Red,\ 4000K,\ direct/indirect\ output,\ Universal\ 120-277V\ /\ 0-10V\ 10\%\ dimming,\ Remote\ driver)$

LX - VE											
PRODUCT CODE	SIZE	SHADE COLOR TEMP OUTPUT		DRIVER / DIMMING		DRIVER TYPE					
VE	s M	Small Ø19.5" x 14.2" / Ø500 x 360mm Medium Ø37.4" x 17.7" / Ø950 x 450mm	Use color codes as shown	30 35 40	3000K 3500K 4000K	D I DI**	Direct Indirect Direct-Indirect	UNV	0 - 10V - 10% dimming (120-277V) (North America only) 1% dimming DSI/DALI (220 - 240V)	RD CD OB	Remote driver Canopy concealed driver On-board driver***
	L	Large Ø60" x 24.4" / Ø1500 x 620mm				26 Lamp holder - 120V AC (North America only) 27 Lamp holder - 220-240V AC (Global)			* Please note the light bulb or driver will not be supplied with the E26/E27 option for this fixture.		

^{**}Direct + Indirect or Indirect output is not currently available for the Small size

***On-Board driver type is not currently available for the Small size

AVAILABLE COLORS

Colors are subject to lead times and variations across batches. Also available in the printed MOTIF collection viewable $\underline{\text{here}}$.

CORE







































Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal, August 2022, LX-Vapor-Echo-Spec Sheet-v6.4



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM WWW.LUXXBOX.COM















TYPE:


PHOTOMETRICS


	SMALL	MED	NUM	LARGE		
Option	Direct OR Indirect	Direct OR Indirect Direct AND Indirect		Direct OR Indirect	Direct AND Indirect	
Total Lumens Delivered	1680 lm	4500 lm 9000 lm		4500 lm	9000 lm	
Wattage	19 W	57W 114 W		57 W	114 W	
Efficacy	88.4 lumens per watt 79 lumens per watt 79 lumens per watt				s per watt	
CRI	90					
ССТ	3000-3500-4000 K					
UGR	<19					

LUMINOUS INTENSITY DISTRIBUTION









LARGE DIRECT-INDIRECT 393 cd Lamp(D)=4500 lm Lamp(I)=4500 lm Max=1573.942 cd Power=114 W 1180 cd


TM-30METRICS


Fidelity Index (Rf): Average similarity to the reference source for all colors Gamut Index (Rg): Average change in chroma for all colors

	SMALL	MEDIUM/LARGE
Rf (Fidelity Index)	90	90.7
Rg (Gamut Index)	100	98.8

COLOR VECTOR GRAPHIC

SMALL MEDIUM/LARGE





Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. August 2022. LX-Vapor-Echo-Spec Sheet-v6.4



LUXXBOX USA INC \times (P)+1 (415) 871 0448 \times USA@LUXXBOX.COM LUXXBOX PTY LTD \times (P)+61 7 3257 2822 \times INFO@LUXXBOX.COM WWW.LUXXBOX.COM













TYPE:

DRIVER INFORMATION

UNIVERSAL 110-277 VAC / 0-10V 10% DIMMING (North America only)						
Size	Output	Wattage	Voltage	Compliance		
SMALL	D	19				
MEDIUM	D	57		FO (1)		
MEDIUM	DI	114	10-55VDC	FC c(UL)us		
LABOR	D	57		LISTED		
LARGE	DI	114				

	GLOBAL 220-240V 1% DIMMING DSI DALI						
Size	Output	Wattage	Voltage	Compliance			
SMALL	D	19					
MEDILIM	D	57		DALL & CR			
MEDIUM	DI	114	6-52VDC				
LARGE	D	57		∅(€			
LARGE	DI	114					


CANOPY INFORMATION


Please note power cord and canopy will always be supplied in black unless specified otherwise.

			UNIVERSAL		(NORTH AMERICA)		GLOBAL			
PRODUCT	SIZE	OUTPUT	RD	ОВ	CD	E26	RD	ОВ	CD	E27
	SMALL	D	SA1	SA2	CD9	SA1	SB1	SB2	CD9	SB1
		D	SA1	SA2	CD9	SA1	SB1	SB2	CD9	SB1
LX-VE	MEDIUM	DI	SA1	SA2	CD13	SA1	SB1	SB2	CD13	SB1
	LADGE	D	SA1	SA2	CD9	SA1	SB1	SB2	CD9	SB1
	LARGE	DI	SA1	SA2	CD13	SA1	SB1	SB2	CD13	SB1











Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. August 2022. LX-Vapor-Echo-Spec Sheet-v6.4



LUXXBOX USA INC \times (P)+1 (415) 871 0448 \times USA@LUXXBOX.COM LUXXBOX PTY LTD imes (P)+61 7 3257 2822 imes INFO@LUXXBOX.COM WWW.LUXXBOX.COM













TYPE:

MATERIAL SPECIFICATIONS

COLOR FASTNESS TO LIGHT:	T: ISO 105-B02-1994 Rating: 6-7			
FIRE TEST:	FIRE TEST: AS 1530.3 / ISO 9705: Group 1 / GB8624 B1 / ASTM E-84-14 (Class A, FSI:20 - SDI:450) / BS EN13501-1:2007+A1:2009 (B-s1, d0)			
ENVIRONMENTAL:	PET achieves GreenTag Certification / GreenRate: Level A			
THERMAL TRANSITION:	ASTM C518-2010. R- Value = 0.30 m ² K/W			
SOUND ABSORPTION:	N: AS ISO 354 – 2006 / Noise reduction coefficient (NRC) = 0.85			
VOC EMISSIONS: ASTM D5116 Rate: < 0.01 mg/m²/hr (7 days)				


Please note some of these certificates will apply to specific colors.


PRODUCT ACOUSTIC PROPERTIES


Testing and post analysis procedures were carried out in accordance with the references detailed below:

AS ISO 354-2006 (R2016)	Acoustics—Measurement of sound absorption in a reverberation room
AS ISO 11654—2002	Rating of sound absorption—Materials and systems
ASTM C423-17	Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method
ASTM E795-16	Standard Practices for Mounting Test Specimens During Sound Absorption Tests
ISO 20189	Screens, furniture and single objects intended for interior use – Rating of sound absorption and sound reduction of elements based on laboratory measurements.

IMPERIAL SABINS	SMALL	MEDIUM	LARGE	
Frequency (Hz)	SIVIALL	MEDIOM		
125	0.44	1.14	2.37	
250	2.43	6.29	13.03	
500	5.39	13.90	28.82	
1000	7.38	19.05	39.49	
2000	7.08	18.28	37.91	
4000	7.38	19.05	39.49	







The Sabin data shown above is in accordance with the latest International Standards for the rating of sound absorption and reduction. This is different from the classic methodology, which includes the calculation of the Noise Reduction Coeficient (NRC), the Sound Absorption Average (SAA), the Weighted Sound Absoption Coefficient (aw) and the Sound Absorption Class (SAC). However, to make it easier to compare against other products, we are including that information on the table on the right, which was calculated using the Horizontal Floor Area method. Fully detailed test reports are available upon request.

NRC	0.75
SAA	0.75
αw	0.6 (MH)

Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. August 2022. LX-Vapor-Echo-Spec Sheet-v6.4


















TYPE:


PRODUCT DIMENSIONS

TOP VIEWS


SMALL




SIDE VIEWS





MEDIUM





LARGE





Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. August 2022. LX-Vapor-Echo-Spec Sheet-v6.4



