

PRODUCT SPECIFICATIONS

Instruct® Desking

March 2021

TECHNICAL SPECIFICATIONS

All Terrain® Instructors' Desk

Stationary unit features a 22" deep x 22" wide and 35 1/2" high storage tower. Tower has three adjustable metal shelves and one laminate rollout shelf at the bottom of the storage unit. Storage tower features a landing pad made of 3/4" laminate with 74P edge and is raised 3 3/4" above the top of the storage tower with aluminum extrusions. Storage tower edges are flush with worksurface.

A 1 1/4" thick laminate covered surface with a 74P edge is attached to the side of the storage tower on one end and is supported by a 4" diameter support leg on the other end of the unit. A perforated partial modesty panel is suspended from the underside of the surface. Modesty panel covers the area from the storage unit to the support leg.

Storage tower features three open grommets and one covered grommet. One grommet is on the top of the storage unit directly below the one covered grommet on the landing pad. Remaining grommets are above and below the worksurface on the inside of the desk unit.

All Terrain® Mobile Instructors' Desk

Unit features an All Terrain binder tower with lectern. There is an open grommet at the top and bottom of left and right sides. Surface is attached to the side of the binder tower and supported on the opposite end by an All Terrain table leg with casters. A perforated partial modesty panel attaches to the leg and the binder tower. Finished height is 40" with lectern.

700 Series® Instructors' Desk

Unit is identical to the standard 700 Series desk with the following changes: (1) Desk has a D shaped top that overhangs the desks frame to allow for collaboration with students; (2) Desk features a 12" deep bookcase opposite the rounded overhang; (3) Desk comes in 66" and 72" lengths. Bookcase is flush with the depth of the desktop. Unit is non-handed, bookcase may be reconfigured after installation.

WorkZone® Instructors' Desk

WorkZone Instructors' desk is based on a standard WorkZone square shoe unit with a worksurface supporting pedestal (BBF configuration) to support the extended side of the square shoe. Opposite side features cantilevered frame. The surface is 1 1/4" thick with a high-pressure laminate.

Instruct® Teachers' Desk with AV Rack

Stand Alone Unit

Unit dimensions are 22" deep x 22" wide with a height of 43.375" for a unit that has a flat lectern top and 44.875" for a unit that has a sloped lectern top. Each unit has one fixed shelf with 6" of clearance above. The back of the shelf is shortened to allow for wire passage. Users have the option of specifying the unit with either a flat or sloped lectern top which is 3/4" laminate with 74P edge. The sloped top has a pencil retainer. There is 3.75" of clearance under the flat top. Units are available with either 3" casters or 3" AT glides. Outriggers are standard on all units.

There are four covered grommets on the shell, two per side. All units have a lockable, removable, vented back panel for access to the computer equipment if the rack option is installed.

Locks are standard on all versions and door types. Two break away keys are provided with each lock. Locks are a high security double-bit design.



TECHNICAL SPECIFICATIONS (CONTINUED)

Teachers' Desk Unit

Unit dimensions are 22" deep x 22" wide with a height of 43.375" for a unit that has a flat lectern top and 44.875" for a unit that has a sloped lectern top. The unit has one fixed shelf with 6" of clearance above. The back of the shelf is shortened to allow for wire passage. Users have the option of specifying the unit with either a flat or sloped lectern top which is ¾" laminate with 74P edge. The sloped top has a pencil retainer. There is 3.75" of clearance under the flat top. Units are available with either 3" casters or 3" AT glides. Outriggers are standard on all units. Desk units are available in an overall length of 60", 66" or 72".

There are two covered grommets on the shell. Both are on the side in which there is a work surface. One grommet is above the work surface and one is below. All units have a lockable, removable, vented back panel for access to the computer equipment if the rack option is installed.

Locks are standard on all versions and door types. Two break away keys are provided with each lock. Locks are a high security double-bit design.

All Terrain® Binder Tower (Lectern Option)

WorkZone Instructors' desk is based on a standard WorkZone square shoe unit with a worksurface supporting pedestal (BBF configuration) to support the extended side of the square shoe. Opposite side features cantilevered frame. The surface is 1 ¼" thick with a high-pressure laminate.

A lectern can be added to any All Terrain binder tower that has both a landing pad and outriggers. Lectern is an angled landing pad to allow better viewing for the instructor.

Binder towers specified without drawers may be optimized for book, binder or bin storage. Units include one adjustable and one fixed shelf. Units may be specified with a single file drawer that can be used for letter files, legal files or bins, or for A4 files. Units with a file drawer include one fixed and one adjustable shelf and may also be specified with pullout pencil tray.

Finish

Units are cleaned thoroughly and subjected to a phosphate etching process before a hybrid epoxy powder paint is applied. Powder paints contain negligible VOC concentrations, less than 3% by weight. During the curing process of the paint, the VOC concentrations are driven off. Thus, the finished powder paint products would emit no significant quantities of VOC once installed.

Locks

Locks are standard and feature a high-security double-bit design, keyed different and core removable. There are 1000 different key combinations possible. Specific key combinations are available at no additional charge; however this information must be included with the order. Locks can be master keyed. All locks have removable and interchangeable plugs for on-site custom keying. To install or remove lock plugs a unique extractor key is required. Two KI "break away" keys are standard with each lock.